



APPLICATION FOR REGISTRATION AS A REGISTERED SERVICE COMPANY
Public Service Commission
SFN 51277 (2/2014)

TYPE OR PRINT - AN INCOMPLETE OR ILLEGIBLE APPLICATION WILL BE REJECTED

Name of Company <i>Quam Petroleum Service, Inc.</i>		Email Address <i>jabiggu@ceesocap</i>		Application Date <i>1/11/16</i>	
Mailing Address <i>4720 Hwy 6</i>		City <i>Mandan</i>		State <i>ND</i>	Zip Code <i>58554</i>
Telephone Number <i>1-701-663-3732</i>		Cell Phone Number <i>1-701-220-1411</i>		Fax Number <i>1-701-663-3650</i>	

Select below all device types your company will certify:

Scales (include maximum capacity, if applicable)	Liquid (include maximum flow rate, if applicable)
<input type="checkbox"/> 1. Rail	<input checked="" type="checkbox"/> 1. Retail Fuel (less than 20 gal. per minute)
<input type="checkbox"/> 2. Truck	<input checked="" type="checkbox"/> 2. High Flow Retail Fuel (20 gal. per minute or greater)
<input type="checkbox"/> 3. Livestock	<input checked="" type="checkbox"/> 3. Vehicle Tank: Max. Flow Rate: _____
<input type="checkbox"/> 4. Hopper: Max. Capacity: _____	<input checked="" type="checkbox"/> 4. Stationary Bulk (fuel or oil): Max. Flow Rate: _____
<input type="checkbox"/> 5. Belt	<input type="checkbox"/> 5. LPG
<input type="checkbox"/> 6. Over 30 lbs.: Max. Capacity: _____	<input type="checkbox"/> 6. Stationary LPG
<input type="checkbox"/> 7. 30 lbs. or less	<input checked="" type="checkbox"/> 7. Fertilizer: Max. Flow Rate: _____
<input type="checkbox"/> 8. Class II (Indicate on your calibration report which weight kit is Class II certified)	<input checked="" type="checkbox"/> 8. Chemical
<input type="checkbox"/> 9. Other: Please List:	<input type="checkbox"/> 9. Anhydrous
	<input type="checkbox"/> 10. Loading Rack
	<input type="checkbox"/> 11. Other: Please List:

List below all persons employed by your company as a North Dakota Registered Service Person and the device types they are registered to certify (attach a separate sheet to list additional employees):

Permit No.	Employee	Device Types Registered to Certify (list using device type numbers from above)
e.g. 1001	e.g. John Doe	e.g. Scales - 2, 3, 6, 8; e.g. Liquid - 1, 2, 6
<i>1604</i>	<i>Jeremiah Quam</i>	<i>Liquid 1, 2, 3, 4, 7, 8</i>
<i>1458</i>	<i>Gerald Quam</i>	<i>Liquid 1, 2, 3, 4, 7, 8</i>

List below all field standards (attach current calibration reports):

1- 100 gallon Determan	S/N 108515826
1- 5 gallon Seraphin	S/N 53469

Additional Application Items (Initial where appropriate):

Standardized Test Report	_____ Copy enclosed
	_____ No change in report filed previously
Tested and Approved Sticker	_____ Copy enclosed
	_____ No change in sticker filed previously
Photocopy of Crimped Lead Wire Seal	_____ Copy enclosed
	_____ No change in crimped lead wire seal filed previously

Public Company Listing:

Include my company information on your registered service company list for public contact.

Yes No

I am Rudipe Luam, and have authority to represent this company. By signing this application, I declare that I have examined this form and accompanying documentation, and to the best of my knowledge and belief, the facts stated and documentation provided is true, correct, and complete.

Rudipe Luam
Signature

Send Completed Application and Related Documents To:

Public Service Commission
 600 E Boulevard Ave Dept 408
 Bismarck ND 58505-0480
 Telephone: (701) 328-2400
 Fax: (701) 328-2410

North Dakota

nd.gov Official Portal for
North Dakota State GovernmentNorth Dakota
LEGENDARY

SECRETARY OF STATE NORTH DAKOTA


[Home](#) | [Business Records Search](#)

QUAM PETROLEUM SERVICE, INC.

Corporation Details

System ID: 11924300 **Phone:** (701) 663-3732
Type: BUSINESS CORPORATION
Status: Active & Good Standing
Original File Date: 12/27/1996 **Effective Date:** 01/01/1997
State of Origin: North Dakota

Nature of Business

BULK FACILITY, INSTALLATION SERVICE OF GAS STATIONS

Principal Office

4720 HIGHWAY 6 MANDAN, ND 58554-8513

Registered Agent

JERALD R QUAM
 4720 HWY 6 S
 MANDAN, ND 58554-8513
 Established Date: Nov 24, 2004

Authorized Shares

Class	Number	Par Value
COMMON	20000.000000	\$1.000000

Generate an Annual Report To File

To Generate a Annual Report form to be filed with the Secretary of State, select the appropriate year of the report you intend to file. This report does not contain details of a report previously filed with the Secretary of State. The annual report years reflected are an indication of the various report forms available in this site and is not an indication that an entity needs to file reports for all years. Missing years indicate that the forms for the missing year have not yet been deployed to the website, or have already been removed, and can be obtained by contacting the Secretary of State.

[2015](#) (generates a forms-fillable pdf in a new pop-up window)

[Return to Search Results](#)

[Contact Us](#)

[Disclaimer](#) | [Privacy Policy](#)

We use Secure Sockets Layer (SSL) encryption technology to ensure your information is secure and protected.

Will open a new window (pop-up).

W3C WAI AA, CSS, XHTML Compliant | Copyright 2006. All Rights Reserved. The State of North Dakota.



Receipt Date: January 14, 2016
Test Date: January 14, 2016
Report Date: January 14, 2016

State Test No.: 335346
Serial No.: 03-53469
Barcode: 202183

Calibration Report

QUAM PETROLEUM SERVICE INC.
4720 NORTH DAKOTA 6
MANDAN, ND 58554
Contact: ARDIS
Phone: 701-663-3732
PO Number: NONE
SOP: 32
Technician ID: 11

Item(s) Submitted: 5 Gallon Measure
Manufacturer: Seraphin
Material: Mild Steel
Equipment Number: None
Condition: Good
Temperature: 19.2 °C
Pressure: 723.8 mmHg
Relative Humidity: 25.8 %
Standard H₂O Temp.: 18.5 °C
Artifact H₂O Temp.: 18.4 °C

Nominal Volume (gal)		Error (in ³)	Volume at Zero Line (gal)	Uncertainty (in ³)	Coefficient of Expansion (°F)
5	As Found	-0.03	4.9999	0.24	0.0000186
	As Left	-0.03	4.9999	0.24	

Neck Calibration: No neck calibration was done at this time.

This measure or prover has been calibrated as a "to contain after wet down" vessel with a pour time of 30 seconds, a drain time of 10 seconds after cessation of full flow and at a reference temperature of 60 °F.

The measure or prover listed above has been compared by volumetric transfer methods to the standards of the State of Minnesota using water as the calibration medium. The standards are traceable to the SI through NIST. Statistical process control charts indicate standards are currently in control. All gauges were sealed in place.

The reported uncertainty conforms to the ISO/IEC Guide to the Expression of Uncertainty in Measurement (2008). The confidence interval is 95%.

Pete Whebbe

Metrologist

Reviewed by:
Mark Nicollet

Quality Manager

Receipt Date: January 14, 2016
Test Date: January 14, 2016
Report Date: January 14, 2016



State Test No.: 335345
Serial No.: 108515826
Barcode: 202182

Calibration Report

QUAM PETROLEUM SERVICE INC.
4720 NORTH DAKOTA 6
MANDAN, ND 58554
Contact: Ardis
Phone: 701-663-3732
PO Number: None
SOP: 33
Technician ID: 19

Item(s) Submitted: 100 Gallon Prover
Manufacturer: Determan
Material: Mild Steel
Description: Dry Bottom
Condition: Good
Temperature: 19.4 °C
Pressure: 723.2 mmHg
Relative Humidity: 27.8 %
Standard H₂O Temp.: 9.1 °C
Artifact H₂O Temp.: 9.1 °C

Nominal Volume (gal)		Tested Volume (gal)	Error (in ³)	Uncertainty (in ³)	Coefficient of Expansion(/°F)
100	As Found	99.995	-1.1	2.4	0.0000186
	As Left	99.995	-1.1	2.4	

Neck Calibration: No neck calibration was done at this time.

This prover has been calibrated as a "to contain after wet down" vessel with a drain time of 30 seconds after cessation of full flow and at a reference temperature of 60 °F.

The prover listed above has been compared by volumetric transfer methods to the standards of the State of Minnesota using water as the calibration medium. The standards are traceable to the SI through NIST. Statistical process control charts indicate standards are currently in control. All gauges were sealed in place.

The reported uncertainty conforms to the ISO/IEC Guide to the Expression of Uncertainty in Measurement (2008). The confidence interval is 95%.

Erik Alfvin

Metrologist

Reviewed by:

Mark Nicollet

Quality Manager

United States Department of Commerce National Institute of Standards and Technology

Certificate of Metrological Traceability For:

Minnesota

This laboratory has demonstrated evidence of an unbroken chain of metrological traceability of its standards to the international system of units (SI), documented measurement uncertainties, uses documented measurement procedures, successfully completed training and proficiency tests, documented calibration intervals, submitted a quality management system, and demonstrated suitable measurement assurance for the Scope listed on this certificate.



The Office of Weights and Measures Program assesses laboratories to NIST Handbook 143 - Program Handbook for State Weights and Measures Laboratories and ISO/IEC 17025:2005.

Scope

2016 to 2017

Mass Echelon II

50 kg to 1 mg
1000 lb to 0.001 lb
4 oz to 0.03125 oz

Weight Carts

10 000 lb to 2000 lb
Wheel Load Weighers
20 000 lb to 2000 lb

Volume Gravimetric, I

20 L to 10 mL
100 gal to 0.25 qt

Mass Echelon III

50 kg to 1 mg
5000 lb to 0.001 lb
4 oz to 0.03125 oz

Railroad Test Cars

110 000 lb to 80 000 lb

Volume Transfer, II

1500 gal to 5 gal
100 gal to 25 gal LPG

A handwritten signature in black ink, appearing to read "Carol T. Hockert".

Carol T. Hockert, Chief
NIST Office of Weights and Measures

Effective Dates: 2016-01-01 to 2017-12-31

Shelly,

Here is a hand copy of our
W+m Decals. They are new ones.

Thank Ardyce

Tested & Approved By

**Quam Petroleum
Service, Inc.**

**4720 Highway 6
Mandan, ND 58554**

**Office: 701-663-3732
Cell: 701-220-1411**

Jan	Feb	Mar	April	May	June
July	Aug	Sept	Oct	Nov	Dec
14	15	16	17	18	19

