



APPLICATION FOR REGISTRATION AS A REGISTERED SERVICE COMPANY
Public Service Commission
SFN 51277 (2/2014)



TYPE OR PRINT - AN INCOMPLETE OR ILLEGIBLE APPLICATION WILL BE REJECTED

Name of Company	Email Address	Application Date	
Rollies Sales & Service Inc	rollies09@gmail.com	2017	
Mailing Address	City	State	Zip Code
P.O. BOX E	OSAKIS	MN	56360
Telephone Number	Cell Phone Number	Fax Number	
320-859-4811	320-859-4812	320-859-3585	

Select below all device types your company will certify:

Scales (include maximum capacity, if applicable)	Liquid (include maximum flow rate, if applicable)
<input type="checkbox"/> 1. Rail	<input checked="" type="checkbox"/> 1. Retail Fuel (less than 20 gal. per minute)
<input checked="" type="checkbox"/> 2. Truck	<input checked="" type="checkbox"/> 2. High Flow Retail Fuel (20 gal. per minute or greater)
<input type="checkbox"/> 3. Livestock	<input checked="" type="checkbox"/> 3. Vehicle Tank: Max. Flow Rate: <u>100</u>
<input type="checkbox"/> 4. Hopper: Max. Capacity: _____	<input checked="" type="checkbox"/> 4. Stationary Bulk (fuel or oil): Max. Flow Rate: <u>100</u>
<input type="checkbox"/> 5. Belt	<input type="checkbox"/> 5. LPG
<input type="checkbox"/> 6. Over 30 lbs.: Max. Capacity: _____	<input type="checkbox"/> 6. Stationary LPG
<input type="checkbox"/> 7. 30 lbs. or less	<input type="checkbox"/> 7. Fertilizer: Max. Flow Rate: _____
<input type="checkbox"/> 8. Class II (indicate on your calibration report which weight kit is Class II certified)	<input type="checkbox"/> 8. Chemical
<input type="checkbox"/> 9. Other: Please List:	<input type="checkbox"/> 9. Anhydrous
	<input type="checkbox"/> 10. Loading Rack
	<input type="checkbox"/> 11. Other: Please List:

List below all persons employed by your company as a North Dakota Registered Service Person and the device types they are registered to certify (attach a separate sheet to list additional employees):

Permit No.	Employee	Device Types Registered to Certify (list using device type numbers from above)
e.g. 1001	e.g. John Doe	e.g. Scales - 2, 3, 6, 8; e.g. Liquid - 1, 2, 6
01	Merwin Roering	1, 2, 3, 4
02	Daniel Nathe	1, 2, 3, 4

List below all field standards (attach current calibration reports):

See Attached	5 gallon
	50 gallon
	100 gallon



Additional Application Items (initial where appropriate):

Standardized Test Report	<input checked="" type="checkbox"/> Copy enclosed <input checked="" type="checkbox"/> No change in report filed previously
Tested and Approved Sticker	<input type="checkbox"/> Copy enclosed <input checked="" type="checkbox"/> No change in sticker filed previously
Photocopy of Crimped Lead Wire Seal	<input type="checkbox"/> Copy enclosed <input checked="" type="checkbox"/> No change in crimped lead wire seal filed previously

Public Company Listing:

Include my company information on your registered service company list for public contact.
 Yes No

I am Julie Fernon, and have authority to represent this company.
By signing this application, I declare that I have examined this form and accompanying documentation, and to the best of my knowledge and belief, the facts stated and documentation provided is true, correct, and complete.

Julie Fernon
Signature

Send Completed Application and Related Documents To:

Public Service Commission
600 E Boulevard Ave Dept 408
Bismarck ND 58505-0480
Telephone: (701) 328-2400
Fax: (701) 328-2410

North Dakota

nd.gov Official Portal for North Dakota State Government



SECRETARY OF STATE NORTH DAKOTA



[Home](#) | [Business Records Search](#)

ROLLIE'S SALES & SERVICE, INC.

Corporation Details

System ID: 27402400	Phone: (320) 859-4811
Type: FOREIGN BUSINESS CORPORATION	
Status: Active & Good Standing	
Original File Date: 07/30/2010	Effective Date: 07/30/2010
State of Origin: Minnesota	

Nature of Business

SERVICE

Principal Office

13790 CO RD 82 SE PO BOX E OSAKIS, MN 56360-0605

Registered Agent

HORIZON RESOURCES
 209 WASHINGTON AVE
 WILLISTON, ND 58801-6035
 Established Date: Oct 07, 2014

Generate an Annual Report To File

To Generate a Annual Report form to be filed with the Secretary of State, select the appropriate year of the report you intend to file. This report does not contain details of a report previously filed with the Secretary of State. The annual report years reflected are an indication of the various report forms available in this site and is not an indication that an entity needs to file reports for all years. Missing years indicate that the forms for the missing year have not yet been deployed to the website, or have already been removed, and can be obtained by contacting the Secretary of State.

[2016](#) (generates a forms-fillable pdf in a new pop-up window)

[Return to Search Results](#)

[Contact Us](#)

[Disclaimer](#)

[Privacy Policy](#)

We use Secure Sockets Layer (SSL) encryption technology to ensure your information is secure and protected.

Will open a new window (pop-up).

W3C WAI AA, CSS, XHTML Compliant | Copyright 2006. All Rights Reserved. The State of North Dakota.

Receipt Date: November 8, 2016
Cal. Date: November 9, 2016
Report Date: November 9, 2016

Report No.: 336729
Serial No.: 29893-5
Barcode: 019857

Calibration Certificate

ROLLIES SALES & SERVICE
HIGHWAY 27 W
OSAKIS, MN 56360-0605
Contact: Marvin Roering
Phone: 320-859-4811
PO Number: None
SOP: 19
Technician ID: 19

Item(s) Submitted: 5 Gallon Measure
Manufacturer: Seraphin
Material: Stainless Steel
Type: Measure
Condition: Good
Temperature: 21.1 °C
Pressure: 742.5 mmHg
Relative Humidity: 42.0 %
Standard H₂O Temp.: 20.4 °C
Artifact H₂O Temp.: 20.4 °C

Nominal Volume (gal)		Calibrated Volume (gal)	Error (in ³)	<i>k</i>	U (in ³)	CCE (°F)
5	As Found	5.0000	-0.01	2.06	0.24	0.0000265
	As Left	5.0000	-0.01			

Neck Calibration: No neck calibration was performed at this time.


This measure has been calibrated as a "to contain after wet down" vessel with a pour time of 30 seconds followed by a drain time of 10 seconds after cessation of full flow.

The vessel listed above has been compared by volumetric transfer methods to the standards of the State of Minnesota using water as the calibration medium. The standards are traceable to the SI through NIST. Statistical process control charts indicate standards are currently in control. All gauges were sealed in place.

All tolerances and specifications were evaluated according to NIST Handbook 105-3 (2010). Uncertainty calculations contain the components in NIST SOP 19 and conform to the ISO/IEC Guide to the Expression of Uncertainty in Measurement (2008), including coverage factors (*k*) calculated at the approximate 95.45 % confidence level. Results apply to item identified in this report only.

CCE is the cubical coefficient of thermal expansion, and the reference temperature is 60 °F
Conversion to SI unit: 1 gallon = 231 in³ = 0.00378541 m³.


Erik Alfvín



Metrologist

Reviewed by:

Mark Nicollet



Quality Manager

Receipt Date: November 16, 2016
Cal. Date: November 16, 2016
Report Date: November 16, 2016

Report No.: 336778
Serial No.: None
Barcode: 019859

Calibration Certificate

ROLLIES SALES & SERVICE
HIGHWAY 27 W
OSAKIS, MN 56306-0605
Contact: Marvin Roering
Phone: 320-859-4811
PO Number: None
SOP: 19
Technician ID: 19

Item(s) Submitted: 50 Gallon Prover
Manufacturer: Unknown
Material: Mild Steel
Type: No Bottom Zero
Condition: Good*
Temperature: 19.5 °C
Pressure: 730.2 mmHg
Relative Humidity: 38.9 %
Standard H₂O Temp.: 15.2 °C
Artifact H₂O Temp.: 15.4 °C

Nominal Volume (gal)		Calibrated Volume (gal)	Error (in ³)	<i>k</i>	U (in ³)	CCE (1/°F)
50	As Found	50.002	0.4	2.13	2.4	0.0000186
	As Left	50.002	0.4			

Neck Calibration: No neck calibration was performed at this time.

***Prover must be painted white per NIST HB 105-3 section 4.6.2.1 and have a permanently-attached ID plate with the information required in 105-3 section 4.3 by the next calibration cycle.**

This prover has been calibrated as a "to contain after wet down" vessel with a drain time of 30 seconds after cessation of full flow.


The vessel listed above has been compared by volumetric transfer methods to the standards of the State of Minnesota using water as the calibration medium. The standards are traceable to the SI through NIST. Statistical process control charts indicate standards are currently in control. All gauges were sealed in place.

All tolerances and specifications were evaluated according to NIST Handbook 105-3 (2010). Uncertainty calculations contain the components in NIST SOP 19 and conform to the ISO/IEC Guide to the Expression of Uncertainty in Measurement (2008), including coverage factors (*k*) calculated at the approximate 95.45 % confidence level. Results apply to item identified in this report only.

CCE is the cubical coefficient of thermal expansion, and the reference temperature is 60 °F


Reviewed by:

Mark Nicollet



Quality Manager

Erik Alfvin



Metrologist

Receipt Date: November 8, 2016
Cal. Date: November 9, 2016
Report Date: November 9, 2016

Report No.: 336730
Serial No.: None
Barcode: 019858

Calibration Certificate

ROLLIES SALES & SERVICE
HIGHWAY 27 W
OSAKIS, MN 56360-0605
Contact: Marvin Roering
Phone: 320-859-4811
PO Number: None
SOP: 19
Technician ID: 19

Item(s) Submitted: 100 Gallon Prover
Manufacturer: Unknown
Material: Mild Steel
Type: No Bottom Zero
Condition: Good*
Temperature: 20.3 °C
Pressure: 745.5 mmHg
Relative Humidity: 40.6 %
Standard H₂O Temp.: 16.1 °C
Artifact H₂O Temp.: 16.2 °C

Nominal Volume (gal)		Calibrated Volume (gal)	Error (in ³)	<i>k</i>	U (in ³)	CCE (°F)
100	As Found	100.004	1.0	2.01	3.3	0.0000186
	As Left	100.004	1.0			

Neck Calibration: No neck calibration was performed at this time.


***Prover must be painted glossy white or a color which is reflective to prevent unnecessary solar heating of product (NIST Handbook 105-3 section 4.6.2.1) by the next calibration cycle.**

This prover has been calibrated as a "to contain after wet down" vessel with a drain time of 30 seconds after cessation of full flow. The vessel listed above has been compared by volumetric transfer methods to the standards of the State of Minnesota using water as the calibration medium. The standards are traceable to the SI through NIST. Statistical process control charts indicate standards are currently in control. All gauges were sealed in place.

All tolerances and specifications were evaluated according to NIST Handbook 105-3 (2010). Uncertainty calculations contain the components in NIST SOP 19 and conform to the ISO/IEC Guide to the Expression of Uncertainty in Measurement (2008), including coverage factors (*k*) calculated at the approximate 95.45 % confidence level. Results apply to item identified in this report only.


CCE is the cubical coefficient of thermal expansion, and the reference temperature is 60 °F
Conversion to SI unit: 1 gallon = 231 in³ = 0.00378541 m³.

Erik Alfvín


Metrologist

Reviewed by:

Mark Nicollet


Quality Manager

United States Department of Commerce
National Institute of Standards and Technology

Certificate of Metrological Traceability For:

Minnesota

This laboratory has demonstrated evidence of an unbroken chain of metrological traceability of its standards to the international system of units (SI), documented measurement uncertainties, uses documented measurement procedures, successfully completed training and proficiency tests, documented calibration intervals, submitted a quality management system, and demonstrated suitable measurement assurance for the Scope listed on this certificate.

The Office of Weights and Measures Program assesses laboratories to NIST Handbook 143 - Program Handbook for State Weights and Measures Laboratories and ISO/IEC 17025:2005.

Scope

Mass Echelon II	Weight Carts	Volume Gravimetric, I
50 kg to 1 mg	10 000 lb to 2000 lb	20 L to 10 mL
1000 lb to 0.001 lb	Wheel Load Weighers	100 gal to 0.25 qt
4 oz to 0.03125 oz	20 000 lb to 2000 lb	Volume Transfer, II
Mass Echelon III	Railroad Test Cars	1500 gal to 5 gal
50 kg to 1 mg	110 000 lb to 80 000 lb	100 gal to 25 gal LPG
5000 lb to 0.001 lb		
4 oz to 0.03125 oz		



2016 to 2017

Carol T. Hoekert, Chief
NIST Office of Weights and Measures

Effective Dates: 2016-01-01 to 2017-12-31