



Coyote Creek
204 County Rd 15
Beulah, ND 58523

Date Sampled: 06/28/12
Date Received: 07/06/12
Date Reported: 08/14/12

Site: CC12015C

Top of coal 121.25' - 85' (depth removed by dragline) = 36.25'

36.25' falls into 35-40' sample interval (0-40' removed by truck shovel fleet)

40' ÷ 5 = 8 sample intervals above dragline removal depth

8 intervals × 20% = 1.6 → 2 intervals of least desirable material

- Only 1 interval has an SAR > 20 and no interval has coarse texture of sandy loam, loamy sand, or sand. More than one interval has an SAR 12-20.

36" projected respread

604 Highway 15 West
P.O. Box 510
Northwood, ND 58267
(701) 587-6010
FAX (701) 587-6013

email: agvise@polarcomm.com
Homepage: www.agvise.com

Ref#	Lab#	Depth	EC	Cat/EC	Ca	Mg	Na	SAR	pH	Texture	Sand	Silt	Clay	Sat. Percent
13251511	36042	0-5 1	5.43	14.95	14.6	27.0	39.5	8.67	7.9	CLAY LOAM	33	30	37	75.9
13251512	36043	5-10 2	8.09	15.37	22.7	39.3	62.3	11.19	7.9	CLAY	23	26	51	102.9
13251513	36044	10-15 3	2.34	9.18	1.3	2.4	17.8	13.05	8.2	CLAY	9	12	79	156.7
13251514	36045	15-20 4	1.90	10.55	1.2	1.8	17.0	13.91	8.0	CLAY	11	32	57	109.5
13251515	36046	20-25 5	1.83	8.14	0.7	1.0	13.2	14.21	8.4	CLAY	5	32	63	160.1
13251516	36047	25-30 6	1.64	10.53	0.9	1.1	15.3	15.46	8.3	CLAY	3	28	69	176.2
13251517	36048	30-35 7	2.64	8.56	1.3	1.3	20.1	17.79	8.2	CLAY	5	22	73	151.3
13251518	36049	35-40 8	2.90	11.71	1.6	1.5	30.9	25.11	7.6	CLAY	23	30	47	85.4
13251519	36050	40-45	1.60	9.99	0.4	0.4	15.2	24.46	8.7	CLAY	9	34	57	211.4
13251520	36051	45-50	1.57	9.86	0.4	0.3	14.9	26.45	8.8	SILT LOAM	21	52	27	127.8
13251521	36052	50-55	1.91	10.43	0.4	0.3	19.2	31.88	8.8	SILTY CLAY LOAM	19	52	29	110.7
13251522	36053	55-60	2.07	9.32	0.4	0.3	18.6	31.07	8.5	LOAM	23	50	27	122.4
13251523	36054	60-65	1.60	10.48	0.3	0.3	16.2	29.28	8.9	CLAY LOAM	21	48	31	124.7
13251524	36055	65-70	1.82	9.20	0.3	0.3	16.1	28.73	8.9	SILTY CLAY LOAM	13	50	37	147.8
13251525	36056	70-75	2.00	10.34	0.4	0.4	19.9	31.53	8.7	CLAY	3	30	67	136.3
13251526	36057	75-80	2.89	11.53	0.8	0.8	31.7	35.67	7.5	CLAY	33	22	45	66.8
13251527	36058	80-85	1.68	10.31	0.3	0.3	16.8	31.65	8.6	CLAY	7	40	53	136.0
13251528	36059	85-90	1.54	10.07	0.3	0.3	15.0	28.74	8.8	SILTY CLAY LOAM	17	48	35	157.9
13251529	36060	90-95	1.53	7.75	0.2	0.2	11.4	25.35	9.1	SILTY CLAY LOAM	15	50	35	182.8
13251530	36061	95-100	1.45	10.79	0.3	0.3	15.0	27.17	8.6	SILTY CLAY LOAM	15	46	39	167.5
13251541	36062	100-105	1.94	8.56	0.3	0.2	16.1	31.48	9.0	LOAM	29	44	27	144.0
13251542	36063	105-110	1.64	10.40	0.3	0.4	16.3	27.55	8.9	CLAY LOAM	29	40	31	143.2
13251543	36064	110-115	2.00	10.02	0.3	0.3	19.4	33.75	8.7	SILTY CLAY	9	44	47	115.3
13251544	36065	115-120	1.91	11.11	0.5	0.4	20.3	30.39	8.5	CLAY	11	20	69	124.5
13251545	36066	120-121.25	1.50	10.54	0.4	0.3	15.1	25.36	7.8	CLAY	37	10	53	109.9
13251546	36067	132-137	1.73	10.36	0.3	0.3	17.3	32.28	8.3	CLAY LOAM	27	38	35	103.0

→ Top of coal
121.25'



Top of coal 110' - 85 (depth removed by dragline) = 25'
 * 0-25' removed by truck shovel fleet.

25' ÷ 5 = 5 sample intervals above dragline removal depth

5 intervals × 20% = 1 interval of least desirable material

- no intervals (0-25') have an SAR > 20 or coarse texture of
 Sandy loam, loamy sand, or sand. More than one interval
 has SAR 12-20

36" projected respread

604 Highway 15 West
 P.O. Box 510
 Northwood, ND 58267

(701) 587-6010
 FAX (701) 587-6013

email: agvise@polarcomm.com
 Homepage: www.agvise.com

Coyote Creek
 204 County Rd 15
 Beulah, ND 58523

Date Sampled: 06/27/12
 Date Received: 07/06/12
 Date Reported: 09/06/12

Site: CC12018C

Ref#	Lab#	Depth	EC	Cat/EC	Ca	Mg	Na	SAR	pH	Texture	Sand	Silt	Clay	Sat. Percent
14366661	35843	0-5 1	3.74	14.50	22.9	17.1	14.3	3.19	7.8	CLAY	19	26	55	81.9
14366662	35844	5-10 2	4.10	12.90	4.4	13.8	34.7	11.48	8.3	CLAY	5	26	69	105.0
14366663	35845	10-15 3	3.82	11.99	3.2	7.5	35.1	15.17	8.3	CLAY	5	26	69	127.3
14366664	35846	15-20 4	2.56	8.17	1.3	1.8	17.8	14.41	8.1	CLAY	3	14	83	143.9
14366665	35847	20-25 5	4.39	12.31	7.8	8.5	37.7	13.23	7.9	SILTY CLAY	15	42	43	107.6
14366666	35848	25-30	2.88	10.60	1.7	2.3	26.6	19.02	8.4	LOAM	31	48	21	59.2
14366667	35849	30-35	2.70	10.15	0.9	1.0	25.4	25.67	8.5	SILTY CLAY LOAM	19	46	35	91.7
14366668	35850	35-40	2.67	10.11	0.7	0.7	25.6	30.21	8.3	CLAY	11	40	49	106.7
14366669	35851	40-45	2.24	10.34	0.4	0.4	22.4	36.06	8.5	SILTY CLAY LOAM	13	48	39	107.1
14366670	35852	45-50	2.83	7.79	0.3	0.3	21.4	37.63	8.6	SILTY CLAY LOAM	17	50	33	94.1
14366671	35853	50-55	2.48	10.09	0.3	0.4	24.3	41.15	8.4	CLAY	15	34	51	93.5
14366672	35854	55-60	2.55	10.12	0.5	0.4	24.9	37.69	8.5	CLAY	11	36	53	101.2
14366673	35855	60-65	3.19	10.39	0.6	0.6	32.0	41.50	7.8	CLAY	13	18	69	87.6
14366674	35856	65-70	2.41	10.39	0.4	0.3	24.3	41.02	8.4	CLAY	15	30	55	116.4
14366675	35857	70-75	1.91	10.35	0.2	0.2	19.3	41.69	8.6	CLAY LOAM	21	42	37	121.3
14366676	35858	75-80	2.19	9.19	0.3	0.3	19.5	34.19	8.5	SILTY CLAY	9	42	49	108.2
14366677	35859	80-85	1.74	10.59	0.3	0.5	17.6	27.33	8.7	SILTY CLAY LOAM	19	46	35	99.0
14366678	35860	85-90	1.52	10.27	0.2	0.4	15.0	28.29	8.9	LOAM	41	32	27	104.7
14366679	35861	90-95	1.45	10.75	0.5	0.8	14.2	17.25	8.6	SILTY CLAY LOAM	19	46	35	149.0
14366680	35862	95-100	1.79	8.46	0.4	0.5	14.2	21.15	8.7	CLAY LOAM	25	40	35	134.0
14366681	35863	100-105	1.52	10.13	0.4	0.5	14.5	21.95	8.6	CLAY	15	36	49	97.8
14366682	35864	105-109	2.04	10.20	0.5	0.5	19.8	27.63	8.5	CLAY	7	20	73	92.0
14366683	35865	121-126	4.25	11.41	2.2	1.5	44.7	32.58	6.7	CLAY	14	11	75	122.0

→ Top of coal
 ~ 110'



Coyote Creek
204 County Rd 15
Beulah, ND 58523

Date Sampled: 06/28/12
Date Received: 07/06/12
Date Reported: 09/06/12

Site: CC12020C

Top of coal 107' - 85' (depth removed by dragline) = 22'

22' falls into 20-25' sample interval (0-25' removed by truck shovel fleet)

$25' \div 5 = 5$ sample intervals above dragline removal depth

5 intervals \times 20% = 1 interval of least desirable material

- no intervals (0-25') have an SAR > 20 or coarse texture of sandy loam, loamy sand, or sand. More than one interval has an SAR 12-20

36" projected respread

604 Highway 15 West
P.O. Box 510
Northwood, ND 58267
(701) 587-6010
FAX (701) 587-6013

email: agvise@polarcomm.com
Homepage: www.agvise.com

Ref#	Lab#	Depth	EC	Cat/EC	Ca	Mg	Na	SAR	pH	Texture	Sand	Silt	Clay	Sat. Percent
13251671	36158	0-5 1	2.50	10.80	6.6	7.4	13.0	4.92	7.9	CLAY LOAM	43	22	35	59.6
13251672	36159	5-10 2	2.50	11.15	1.5	3.9	22.4	13.55	8.4	CLAY	15	32	53	79.3
13251673	36160	10-15 3	4.35	12.70	4.9	8.6	41.8	16.09	7.0	CLAY	17	36	47	85.3
13251674	36161	15-20 4	4.19	11.46	4.2	5.9	37.9	16.84	7.9	SILTY CLAY LOAM	19	42	39	111.2
13251675	36162	20-25 5	3.35	10.74	2.0	3.0	31.0	19.56	8.1	SILTY CLAY	13	42	45	130.9
13251676	36163	25-30	2.24	10.09	0.7	1.1	20.8	22.03	8.5	SILTY CLAY LOAM	19	50	31	133.8
13251677	36164	30-35	5.60	13.06	2.1	3.1	68.0	42.39	8.6	LOAM	41	34	25	112.5
13251678	36165	35-40	2.48	10.78	0.9	0.9	25.0	26.63	8.4	CLAY LOAM	23	44	33	127.7
13251679	36166	40-45	2.40	9.43	0.4	0.6	21.6	30.42	8.6	SILTY CLAY LOAM	17	52	31	132.5
13251680	36167	45-50	2.97	7.40	0.5	0.5	21.0	30.20	8.8	CLAY LOAM	21	44	35	127.3
13251681	36168	50-55	1.97	9.65	0.3	0.3	18.3	31.35	9.0	LOAM	41	34	25	130.2
13251682	36169	55-60	1.64	11.47	0.4	0.3	18.1	30.81	9.0	LOAM	41	36	23	115
13251683	36170	60-65	2.82	10.93	0.8	0.7	29.3	33.21	8.0	CLAY	15	26	59	136.5
13251684	36171	65-70	2.36	10.63	0.5	0.4	24.1	35.48	8.5	CLAY	13	34	53	126.1
13251685	36172	70-75	1.63	10.07	0.3	0.3	15.8	28.54	9.0	CLAY LOAM	23	40	37	164.5
13251686	36173	75-80	1.93	9.30	0.4	0.4	17.2	29.01	8.8	SILTY CLAY LOAM	13	48	39	168
13251687	36174	80-85	2.00	10.57	0.4	0.3	20.4	34.76	8.7	CLAY	7	36	57	144.2
13251688	36175	85-90	1.77	10.31	0.3	0.3	17.7	32.22	8.8	SILTY CLAY	15	42	43	176.3
13251689	36176	90-95	1.75	10.44	0.3	0.3	17.7	31.96	8.8	SILTY CLAY LOAM	19	44	37	150
13251690	36177	95-100	2.06	8.64	0.3	0.3	17.2	32.66	8.7	CLAY	15	40	45	140.8
13251692	36178	100-105	1.86	10.42	0.3	0.3	18.8	35.66	8.6	CLAY	5	28	67	139
13251693	36179	105-107	1.00	11.87	0.3	0.6	11.0	16.33	8.5	CLAY	5	22	73	131
13251694	36180	118-123	1.73	10.39	0.3	0.4	17.3	29.39	7.7		Not enough sample			127.8

→ Top of coal
107'